## Contemporary Acoustic Guitar Design and Build, Vols 1 and 2

Book · O	ctober 2023	
CITATIONS		READS
8		2,845
2 author	s, including:	
	Trevor Gore	
0	Gore Guitars	
	7 PUBLICATIONS 50 CITATIONS	
	SEE PROFILE	

## **Design Volume - Table of Contents**

Acknowledgements Reviews Forewords to 1<sup>st</sup> and 2<sup>nd</sup> Editions Preface Introduction

1.		les of Vibration and Acoustics for Guitar Designers	
	1.1. Soı	und and How We Hear	
	1.1.1.	What is sound?	. 1-2
	1.1.2.	The ear	. 1-6
	1.1.2.1		
	1.1.2.2	2. Roughness	. 1-9
	1.1.2.3	B. Masking	1-12
	1.1.3.	Consequences for guitar designers of how we hear	1-15
	1.1.4.	Section summary	1-16
	1.2. Sin	nple harmonic motion	
	1.2.1.	Mathematical definition of simple harmonic motion	
	1.2.2.	Geometrical model of simple harmonic motion	
	1.2.3.	The period of simple harmonic motion	
	1.2.4.	An example of simple harmonic motion	
	1.2.5.	The energy embodied in simple harmonic motion	
	1.2.6.	Section summary	1-22
		roduction to the mechanics of beams	
	1.3.1.	Stiffness of simple beams	
	1.3.2.	The mass of a simple beam	
	1.3.3.	Vibrating systems	
	1.3.4.	Section summary	
		sonance and vibration sensitivity	
	1.4.1.	Simple resonators	
	1.4.2.	The Helmholtz resonator	
	1.4.3.	Damped simple resonators	
	1.4.4.	Driven, damped simple resonators – strings driving soundboards	
	1.4.5.	The O Factor	
	1.4.6. 1.4.7.	The Q-Factor	
	1.4.7.	Mechanical Impedance	
	1.4.9.	Impedance (mis)macching Impedance, admittance and the high performance guitar	
	1.4.10.	Beats	
	1.4.11.	Section Summary	
		rations in strings and the forces they exert	
•	1.5.1.	Types of waves in strings – frame of reference	
	1.5.2.	Transverse waves in strings	
	1.5.3.	Wave partials and harmonicity	
	1.5.4.	Waves in "ideal" strings	
	1.5.5.	Forces on the terminations of an ideal string	
	1.5.6.	Real strings	
	1.5.7.	Plucking at places other than the centre	
	1.5.8.	Forces exerted by a string on a soundboard	
	1.5.9.	Strings with bending stiffness	
	1.5.10.	Section summary	
	1.6. Int	roduction to vibrations of bars and plates – strings driving soundboards	
	1.6.1.	Vibrations of bars	
	1.6.2.	Vibrations of plates with free edges	
	1.6.3.	Vibrations of flat plates fixed around their edges	
	1.6.4.	Guitar vibration modes excited by the string forces	
	1.6.5.	Vibrations of curved plates (spherical shells)	
	1.6.6.	Section Summary	
		und radiation from a guitar	
	1.7.1.	How sound is radiated by a guitar	1-81
	1.7.2.	Monopole sound radiation and specific mobility	
	1.7.3.	Monopole mobility and the frequency response curve	
	1.7.4.	The anatomy of a plucked note	1-92
	1.7.5.	Sound radiation from the guitar cavity at middle frequencies	1 - 93

	1.7.6.	Sound radiation and directivity	
	1.7.7.	Section summary1	-100
2.	Analyt	ical Guitar Models and their Use	2-2
		upled resonators and simple low frequency guitar models	
		upled resonators	
	2.2.1.	Two mass coupled resonator	. 2-4
		OOF model of a guitar's low frequency response	
		Low frequency response of a guitar with a stiff back	
		Two mass coupled resonator model for guitars	
		Using the 2-DOF model to determine $f_h$	
	2.3.4.	Direct determination of the Helmholtz frequency	
	2.3.5.	Use of the 2-DOF model in the workshop	
		Using the 2-DOF model for guitars with live backs	
	2.3.7. 2.3.8.	Some unusual features of guitar shaped cavities	
	2.3.6.	Coupled top plate and back plate guitar model	
		Target values for the main top and main air resonances	
		Investigative modelling – working in the frequency domain	
	2.3.12		
	2.3.12	· · ·	
	2.4. Sim	nulation of a guitar's frequency response	
		A 4-DOF model of low frequency guitar function	
	2.4.1.1		
	2.4.1.2		
	2.4.2.	The behaviour of superimposed simple sound sources	
	2.4.3.	Combining the 4-DOF model with superimposed simple sources	
		upling of strings to soundboards	
	2.6. Cha	apter Summary	.2-51
_			
3.	The De	esign Objective - The Perfect Guitar	3-2
		ayability	
	3.1.1. 3.1.2.	Plucking hand feel	
	3.1.2.		
	3.1.2.2		
	3.1.2.3	•	
	3.1.2.4		
	3.1.2.5		
	3.1.2.6		
	3.1.2.7		
	3.1.2.8		
	3.1.2.9	P. Neck finish	3-14
	3.1.2.1		
	3.1.2.1		
		usicality	
	3.2.1.	Consonance and dissonance	
	3.2.1.1		
	3.2.1.2		
	3.2.1.3		
	3.2.1.4		
	3.2.1.5	, , , , , , , , , , , , , , , , , , , ,	
	3.2.1.6 3.2.1.7	<b>5</b> ', ', ', ', ', ', ', ', ', ', ', ', ',	
	3.2.1.7	The acoustic response characteristics of a guitar	
	3.2.2.		
	3.2.2.2		3-29
	3.2.2.3		
	3.2.2.4		
	3.2.2.5		
	3.2.2.6		
	3.2.2.7	, ,	
	_	oncluding remarks	
		-	

4.	Component Design	
	4.1. Wood as an organic material	4-2
	4.1.1. The composition of wood	4-3
	4.1.2. The annual cycle	
	4.1.3. Dealing with moisture	4-5
	4.1.4. Dealing with runout	
	4.1.5. Storing wood	
	4.2. Guitar woods	
	4.2.1. Top woods	
	4.2.2. Back and side woods	
	4.2.3. Neck woods	
	4.2.4. Brace woods	
	4.2.5. Fretboard woods	
	4.2.6. Bridge woods	
	4.2.7. Woods for other components	
	4.3. Wood properties that matter	
	4.3.1. The sound radiation coefficient	4-19
	4.3.2. The damping factor	
	4.3.3. Measuring wood properties	4-21
	4.3.3.1. Measurement of Q	
	4.3.3.2. Measurement of logarithmic decrement	
	4.3.3.3. Potential difficulties	
	4.3.3.4. Long grain damping vs. cross grain damping	
	4.3.3.5. Tap testing for "Q"	
	4.3.4. Conditioning wood	
	4.3.5. Section summaries, sections 4.1, 4.2 and 4.3	
	4.4. Design of braces and bracing systems	
	4.4.1. Bending stiffness	
	4.4.2. Brace design criteria	
	4.4.3. Calculating the second moment of area of a brace	
	4.4.4. Measurement of Young's modulus E for brace material	
	4.4.5. Determination of soundboard flexural rigidity	
	4.4.6. Carbon fibre reinforced braces	
	4.4.6.1. Designing Composite Braces	
	4.4.6.2. Balancing brace stiffness to panel stiffness	
	4.4.7. Stress limits for braces	
	4.4.8. Top bracing layout - guidelines	
	4.4.9. Back bracing	
	4.4.10. Section summary	
•		
	4.5.1. Waves in plates	
	5	
	4.5.3. Establishing the target plate thickness	4-60
	4.5.4. Sensitivity to long and cross grain stiffness variations	
	4.5.5. Panel design decisions	
	4.5.6. Section summary	
•	4.6. Body shapes and the design of other components	
	4.6.1. Bridge design	
	4.6.1.1. The bridge as a distributor of string loading	
	4.6.1.2. Positioning the bridge on X-braced guitars	
	4.6.1.3. Bridge mass and stiffness	
	4.6.1.4. Steel string bridge detail design	
	4.6.1.5. The bridge plate	
	4.6.1.6. Classical guitar bridges	
	4.6.2. Linings	
	4.6.3. End blocks	
	4.6.4. Cutaways	
	4.6.5. Neck joint	
	4.6.6. Fretboard - fret spacing	
	4.6.7. Neck cross sectional shape	
	4.6.8. Truss rods	
	4.6.9. The nut	
	4.6.10. Headstock	4-81

4.6.11. Body shape	4-84
4.6.11.1. Size and shape	
4.6.11.2. Body shape proportions	
4.6.11.3. Designing body shapes	
4.6.12. Neck angle, neck relief and top curvature	4-89
4.6.12.1. The effect of action adjustments	
4.6.12.2. The effect of fretboard relief	
4.6.12.3. The effect of soundboard doming	
4.6.13. Section summary	
4.7. Intonation	
4.7.1. A first source of intonation errors	
4.7.1. A first source of intonation error	
4.7.2.1 Fixing intonation errors due to body resonances	
4.7.2.1. Fixing intollation errors due to body resolidnces	4-99
4.7.2.2. Resonance shifting	
4.7.2.3. Empirical nut and saddle compensation	
4.7.2.4. A simple intonation fix	
4.7.3. Compensation for a high performance guitar	
4.7.3.1. Measuring a string's longitudinal stiffness	
4.7.3.2. Calculating the change in path length as the string is fretted	
4.7.3.3. The effect of string bending stiffness on intonation error	
4.7.4. Compensation without most of the mathematics	
4.7.5. Compensation with even less mathematics	
4.7.6. Nut compensation and the neck layout	
4.7.7. Section summary	
4.8. The visual aesthetic	4-123
5. Layout Procedure	
5.1. Drafting the layout of a steel string guitar	
5.2. Drafting the layout of a classical guitar	
5.3. Section summary	5-7
AT 4 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	
AI 1. Technical note on collecting spectrographic data	
AI 2. Using Chladni's technique to visualise vibration modes	
AI 3. Collecting Monopole mobility data	AI-7
ATT 1 Deficition of the country and an expellent on the classification for the	A TT - 1
AII 1. Deflection of the soundboard under oscillating longitudinal string forces	AII-I
AII 2. 4 Degree of Freedom model of low frequency guitar function	
AII 3. Fretboard Curvature	AII-11
AIII 1. Frequency look-up table	Λ T T T _ 1
AIII I. Frequency look-up table	AIII-1
AIV 1. Bending waves on plates	AIV-1
AV 1. Sources of residual intonation errors, saddle-only compensation	AV-1
AV/7.4 G	
AVI 1. Set-up and Performance Parameters of Guitars	AVI-1
Glossary	
UIUSSAI V	

References

Index

About Trevor and Gerard

## **Build Volume - Table of Contents**

Acknowledgements Reviews Forewords to 1<sup>st</sup> and 2<sup>nd</sup> Editions Preface

1.	Introdu	ction	. 1-2
2.	Δ Brief	Review of Assembly Systems	2-2
2.1.		assembly methods	
2.2.		trained assembly methods	
۷.۷.	COIIS	tialiled assembly illethous	. Z- <del>T</del>
3.	Our An	proach to Building	3_3
3.1.		building system	
		he outside mould	
		he use of dishes and go-bar decks	
		he bolt-on neck	
		rder of construction	
_		ssembly flow chart	
5.1	A	SSETTIDITY TOW CHart	. 5-9
4. V	Norksho	p, Tools, Equipment and Jigs	4-2
4.1.		workshop and humidity control	
4.2.		onary machinery	
4.3.		l power tools	
4.4.		l edge tools	
4.4		tandard bench planes	
		lock planes	
		inger planes	
4.4		igh angle planes	
4.4		crapers	
4.4		haves	
4.4		hisels	
		aws	
		asps, microplanes and files	
		anding blocks	
4.5.		pening tools and process	
4.6.		suring instruments and marking tools	
4.7.		ps	
		pring clamps	
		- clamps	
		i - clamps	
		nstrument maker's clamps	
		rigger action clamps	
		arallel screw clamps	
4.8.		ial tooling, fixtures and jigs	
		ody shape template	
4.8		ody mould	
4.8		o-bar deck	
4.8	3.4. D	ished work boards	4-26
4.8		ide bending equipment	
4.8		inding ledge routing machine	
4.8		anel joining fixture	
4.8		ench accessories	
4	1.8.8.1.	Bench hooks	
4	1.8.8.2.	Shooting board	
	1.8.8.3.	Panel planing board	
	1.8.8.4.	Thickness gauge	
4	1.8.8.5.	Neck carving horse	
4.8	3.9. R	outing aidsouting aids	4-43
4	1.8.9.1.	A custom fence for routing bridges	4-45
	1.8.9.2.	A trammelling router base for circle cutting	

4.8.9.3. A simple router table	4-45
4.8.9.4. Rectangular work board	4-45
4.8.9.5. Bridge routing jig	4-47
4.8.9.6. Body mortise routing fixture	
4.8.9.7. Brace bottom curve routing fixture	
4.8.10. Neck bolt drilling jig	
4.8.11. Neck tapering fixture	
4.8.12. Classical headstock barrel boring jig	
4.8.13. Fretboard caul	
4.8.14. String spacing tool for nut layouts	
4.9. Glues and general gluing practice	
4.9.2. Gluing practice	
4.10. Finishes	
4.11. Craftsmanship counts	4-55
5. The Neck	
5.1. Building the neck blank	
5.2. Cutting the truss rod slot	5-9
5.2.1. Marking out the truss rod slot	5-9
5.2.2. Routing the truss rod slot	5-9
5.3. Cutting the neck tenon	
5.3.1. Marking out the neck tenon	
5.3.2. Making the cuts	
5.5.2. Fluxing the cuts	13
6. Joining and Thicknessing the Panels	6-2
6.1. Squaring and surfacing the panels	
6.3. Joining the panels	
6.3.1. Shooting the edges – top and back panels	
6.3.2. Joining the panels	
6.4. Rosette making	
6.4.1. A traditional rosette for a steel string guitar	
6.4.1.1. Making the rosette former	6-11
6.4.1.2. Squaring the ends of the shell segments	6-11
6.4.1.3. Assembling the shell ring	6-13
6.4.1.4. Inlaying the rosette into the soundboard	
6.4.1.5. Levelling the rosette	
6.4.2. A contemporary rosette for steel string or classical guitar	
6.4.2.1. Producing a burl slice	
6.4.2.2. Routing the rosette blank	
6.4.2.3. Inlaying the rosette into the soundboard	
6.5. Final thicknessing	
<del>-</del>	
6.6.1. Assembling and shaping the patch blank	
6.6.2. Gluing down the sound hole patch	
6.7. Cutting out the sound hole	6-31
6.7.1. Tapering the inside edge of the sound hole	
6.8. Thicknessing the sides	6-31
7. Making Braces	7-2
7.1. Preparing back braces and conventional X-braces for tops	
7.1.1. Machining the curve on the base of the brace	
7.1.1.1. Router method	
7.1.1.2. Hand tool method	
7.2. Making lattice bracing	
7.3. Making falcate braces	
7.3.2. Bending the laminates	
7.3.3. Trimming the braces to size	
7.3.4. Tertiary braces and sound hole bracing	
7.3.5. Upper transverse brace	
7.3.6. The bridge plate	7-13
7.3.0. The bridge plate	

8. 8.			he Sidesng the sides for bending	
8.			bending iron	
_			side bending machine	
			g a Venetian cutaway	
8.			the sides to the mould	
	8.5.1.		a non-cutaway guitar	
	8.5.2.		a cutaway guitar	
			, 3	
9.	Ma	king th	e End Blocks and Linings	9-2
9.	1.	Making	the tail block	9-2
9.	2.	Making	the standard bolt-on head block	9-4
9.	3.	Making	the bolt-on, bolt-off head block for a Vene	etian cutaway 9-5
9.	4.		the linings	
	9.4.1.		paring top linings	
	9.4.2.	Pre	paring back linings	9-9
9.			side splints	
9.	6.	Making	the mass support blocks	9-11
10.	As		g the Sides, End Blocks and Linings	
10	0.1.		in the end blocks	
	10.1.1		a non-cutaway guitar	
			a cutaway guitar	
			the linings	
			king the reference lines	
	10.2.2		alling the laminated top linings	
	10.2.3		ng the tail block splint	
	10.2.4		king out and trimming the side profile to to	
	10.2.5		alling the back linings	
	10.2.6		ng the side splintsking out and trimming the side profile to to	
	10.2.7	. Mai	king out and trimining the side prome to ta	ake the top paner10-13
11	Brad	ring the	Panels	11_2
			the back	
			ially braced "Live" back	
		l.1.1.	Installing the marriage strip	
		1.1.2.	Shaping the marriage strip	
		1.1.3.	Letting in the transverse braces	
		1.1.4.	Gluing in the braces	
		1.1.5.	Scalloping the back braces	
	11.1.2	2. Lad	der braced back	
11	1.2.	Bracing	the top	11-11
	11.2.1	L. Bra	cing styles	11-11
	11.2.2	2. X-b	raced top	
	11.2	2.2.1.	Layout the brace positions	11-16
		2.2.2.	Bridge plate and upper transverse brace	
		2.2.3.	Fitting the X-braces	
		2.2.4.	The upper and lower face braces	
		2.2.5.	The finger braces	
		2.2.6.	Carving the braces	
		2.2.7.	Carving the finger braces and face braces	
		2.2.8.	Carving the X-joint	
		2.2.9.	Scalloping the outboard ends of the brace	
		2.2.10. 2.2.11.	Tapering the braces The linen patch	
		2.2.11.	The sound hole braces	
		2.2.12.	Note on J45 back bracing	
		2.2.13. 2.2.14.	Note on post-finishing brace tuning	
			braced top	
		2.3.1.	Layout the brace positions	
		2.3.2.	The fan braces	
		2.3.3.	Arching the bottoms of the braces	
		2.3.4.	Making the bridge plate	
		2.3.5.	Rebating the fan braces	

11.2.3.0	6. Gluing on the bridge plate
11.2.3.	
11.2.3.8	
11.2.3.9	
11.2.3.	
11.2.3.	
11.2.3.	, ,
11.2.3.	
	Lattice braced top
11.2.4.	
11.2.4.	
11.2.4.	
11.2.4.4	
11.2.4.	5
11.2.4.0	
	Falcate braced top for a 12 <sup>th</sup> fret neck joint steel string guitar
11.2.5.	
11.2.5.	
11.2.5.3	
11.2.5.4	
11.2.5.	
11.2.5.0	
11.2.5.	7. The upper transverse brace
11.2.5.8	8. Note on back bracing for falcate braced guitars
12. Assem	bling the Top, Back and Sides12-2
	Il shaping of the sides' top and back edges12-2
	ng the back panel12-4
	ng the top panel12-6
12.4. Glui	ng the back panel to the sides12-11
	cking the neck geometry12-13
	ng the soundboard to the sides12-16
	nning the edges of the top panel12-18
	g and daged of the top panel
13. Bindin	g and Purfling13-2
	ing the bindings13-2
	ting the binding and purfling rebates13-6
	Planning the binding and purfling13-6
	Cutting the stepped rebate13-6
	ding and fitting the bindings and purfling13-9
	lying the binding and purfling
	elling the bindings
	e on fitting shell purfling
	ng the tail strip
	Making the tail strip
13./.2.	Chiselling the tail strip channel
	eck, Part 2; Fitting and Preliminary Shaping14-2
	ing up the guitar in the holding fixture14-2
	ting the body mortise14-5
	ng the neck14-5
	Adjusting the tenon for width14-5
	Trimming the tenon to length and depth14-7
	Correcting the yaw angle14-7
	Correcting the pitch angle14-7
14.3.5. l	Drilling the mortise for the bolt bar14-11
	ing the holes for the head block bolts14-13
14.5. Cou	nterboring the head block14-13
14.6. Drill	ing the bolt holes in the neck14-16
	iminary shaping of the neck14-18
	Establishing the longitudinal thickness taper14-18
	Thicknessing the headstock
	Blending the head/neck curves14-20
14.7.4.	Preliminary carving of the heel14-20

	Making the Fretboard	
15.1.		
	Cutting the fret slots	
_	2.1. Fret slot spacing	
	2.2. Low technology fret slotting	
	2.3. Higher technology fret slotting	
	B.1. Nut ledge for a fully compensated nut	
	B.2. Nut ledge with no nut compensation	
15.4.	Crowning the fretboard	
15.5.	Tapering the fretboard	
15.6.		
	5.1. Choice of fret wire	
	5.2. Preparing the fretboard for fretting	
15.6	5.3. Pressing in frets	15-13
	5.4. Hammering in frets	
15.7.	Trimming the body end of the fretboard	15-15
	The Bolt-On, Bolt-Off Neck Joint	
16.1.	Routing the neck extension pocket	
16.2.	Re-establishing the truss rod groove in the neck extension	
16.3.	Fitting the T-nuts to the neck extension	
16.4.	Special requirements for the bolt-on bolt-off neck for classical guitars	16-9
17. N	Naking the Adjustable Truss Rod	17-2
	The single acting truss rod	
	1. Making the adjusting nut	
	2. Making the stop block	
	3. Making the truss rod	
	The double acting truss rod	
-7		
10 7		
18. T	The Neck Part 3; The Headstock, Fretboard Gluing, Final Carving and Heel	Cap .18-2
18.1.	he Neck Part 3; The Headstock, Fretboard Gluing, Final Carving and Heel Adding the ears	
		18-2
18.1.	Adding the ears	18-2 18-2 18-3
18.1. 18.2. 18.3. 18.4.	Adding the ears  Making the headstock laminate	18-2 18-2 18-3
18.1. 18.2. 18.3.	Adding the ears	18-2 18-2 18-3 18-3
18.1. 18.2. 18.3. 18.4. 18.5. 18.6.	Adding the ears	18-2 18-3 18-3 18-7 18-9
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7.	Adding the ears	18-2 18-3 18-3 18-7 18-9
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7.	Adding the ears	18-2 18-3 18-3 18-7 18-9 18-11
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7	Adding the ears	18-218-318-718-918-11
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8.	Adding the ears	18-218-318-318-718-918-1118-11
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9.	Adding the ears	18-218-318-318-718-918-1118-1118-18
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9.	Adding the ears	18-218-318-318-718-918-1118-1118-18
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  0.1. Final fitting of the standard neck to the body	18-218-318-718-918-1118-1118-1818-18
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9. 18.9.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  9.1. Final fitting of the standard neck to the body	18-218-318-718-918-1118-1118-1818-1818-18
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9. 18.9. 19. F	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  1. Squaring the neck  2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  1. Final fitting of the standard neck to the body  Surface preparation	18-218-318-718-918-1118-1118-1818-1219-2
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9. 18.9. 18.9. 19. F	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  1.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling	18-218-318-318-718-918-1118-1118-1818-1819-219-2
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.1. 19.2. 19.2	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  2.1. Squaring the neck  2.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  2.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler	18-218-318-318-718-918-1118-1118-1818-1219-219-2
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19. 19. 19.2. 19.2. 19.2	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  3.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler  2.2. Using an epoxy fill	18-218-318-318-718-918-1118-1118-1818-2119-219-219-419-6
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.2.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  1.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler  2.2. Using an epoxy fill  2.3. A note on sanding technique	18-218-318-318-718-918-1118-1118-1818-2119-219-219-419-619-8
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.2. 19.3.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  1.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler  2.2. Using an epoxy fill  2.3. A note on sanding technique  Finish application	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-8
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.2. 19.3. 19.3.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  1.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler  2.2. Using an epoxy fill  2.3. A note on sanding technique  Finish application  3.1. Equipment set up and technique	18-218-318-318-718-1118-1118-1118-1819-219-219-419-619-819-9
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.2. 19.3. 19.3. 19.3.	Adding the ears  Making the headstock laminate Gluing the headstock  Fitting the tuning machines Gluing on the fretboard Shaping the neck 7.1. Squaring the neck 7.2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers 0.1. Final fitting of the standard neck to the body  Finishing Surface preparation Grain filling 1.1. Using a traditional oil-based grain filler 1.2. Using an epoxy fill 1.3. A note on sanding technique Finish application 3.1. Equipment set up and technique 3.2. Spraying pattern and schedule	18-218-318-318-718-918-1118-1118-1818-2119-219-219-419-619-819-919-9
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.1. 19.2. 19.2 19.2 19.3. 19.3. 19.3. 19.4.	Adding the ears.  Making the headstock laminate Gluing the headstock laminate Shaping the headstock Fitting the tuning machines Gluing on the fretboard Shaping the neck 7.1. Squaring the neck 7.2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers 9.1. Final fitting of the standard neck to the body Finishing. Surface preparation Grain filling 9.1. Using a traditional oil-based grain filler 9.2. Using an epoxy fill 9.3. A note on sanding technique Finish application 8.1. Equipment set up and technique Sanding and buffing.	18-218-318-318-718-918-1118-1118-1818-2119-219-419-619-819-919-9
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.2. 19.3. 19.3. 19.3.	Adding the ears.  Making the headstock laminate Gluing the headstock laminate Shaping the headstock Fitting the tuning machines Gluing on the fretboard Shaping the neck  1. Squaring the neck 2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers  1. Final fitting of the standard neck to the body  Surface preparation Grain filling  1. Using a traditional oil-based grain filler  2. Using an epoxy fill  3. A note on sanding technique Finish application  3.1 Equipment set up and technique.  Sanding and buffing. French polishing a guitar top.	18-218-318-318-718-918-1118-1118-1818-2119-219-419-619-819-919-919-919-11
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.1. 19.2. 19.2 19.2 19.3 19.3 19.3 19.4. 19.5. 19.6.	Adding the ears  Making the headstock laminate  Gluing the headstock laminate  Shaping the headstock  Fitting the tuning machines  Gluing on the fretboard  Shaping the neck  7.1. Squaring the neck  7.2. Drafting the cross sectional profile of the neck  Fitting the heel cap  Installing the fret markers  7.1. Final fitting of the standard neck to the body  Finishing  Surface preparation  Grain filling  2.1. Using a traditional oil-based grain filler  2.2. Using an epoxy fill  2.3. A note on sanding technique  Finish application  3.1. Equipment set up and technique  Sanding and buffing  French polishing a guitar top  Advanced shellac pore-fill and finish	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-919-919-919-11
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.1. 19.2. 19.2 19.2 19.3 19.3 19.3 19.4. 19.5. 19.6.	Adding the ears	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-919-919-919-1119-13
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.1. 19.2. 19.2. 19.2. 19.3. 19.3. 19.4. 19.5. 19.6.	Adding the ears  Making the headstock laminate Gluing the headstock laminate Shaping the headstock Fitting the tuning machines Gluing on the fretboard Shaping the neck 2.1. Squaring the neck 2.2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers 3.1. Final fitting of the standard neck to the body Finishing Surface preparation Grain filling 2.1. Using a traditional oil-based grain filler 2.2. Using an epoxy fill 3.3. A note on sanding technique Finish application B.1. Equipment set up and technique B.2. Spraying pattern and schedule Sanding and buffing French polishing a guitar top Advanced shellac pore-fill and finish 6.1. The shellac mix 6.2. The application pad	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-919-919-1119-1319-1519-15
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.3. 19.3. 19.3. 19.5. 19.6. 19.6.	Adding the ears.  Making the headstock laminate Gluing the headstock laminate Shaping the headstock Fitting the tuning machines Gluing on the fretboard Shaping the neck 7.1. Squaring the neck 7.2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers 9.1. Final fitting of the standard neck to the body Finishing Surface preparation Grain filling 9.1. Using a traditional oil-based grain filler 9.2. Using an epoxy fill 9.3. A note on sanding technique Finish application 8.1. Equipment set up and technique Finish application 8.2. Spraying pattern and schedule Sanding and buffing French polishing a guitar top Advanced shellac pore-fill and finish 6.1. The shellac mix 6.2. The application pad 6.3. Hardware and abrasives	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-919-919-1119-1319-1519-15
18.1. 18.2. 18.3. 18.4. 18.5. 18.6. 18.7. 18.7. 18.8. 18.9. 18.9. 19.2. 19.2. 19.2. 19.3. 19.3. 19.3. 19.5. 19.6. 19.6. 19.6.	Adding the ears.  Making the headstock laminate Gluing the headstock laminate Shaping the headstock Fitting the tuning machines Gluing on the fretboard Shaping the neck  7.1. Squaring the neck 7.2. Drafting the cross sectional profile of the neck Fitting the heel cap Installing the fret markers  7.1. Final fitting of the standard neck to the body  Finishing Surface preparation Grain filling  7.1. Using a traditional oil-based grain filler  7.2. Using an epoxy fill  7.3. A note on sanding technique Finish application  7.4. Equipment set up and technique Finish application  7.5. Spraying pattern and schedule Sanding and buffing French polishing a guitar top Advanced shellac pore-fill and finish  7.6.1. The shellac mix  7.7. The application pad  7.8. Ardware and abrasives	18-218-318-318-718-918-1118-1118-1818-1819-219-219-419-619-919-919-1119-1519-1519-15

20. The Bridge and Saddle	
20.2. Construction of a contemporary bridge for a classical guitar	20-10
20.3. Construction of a contemporary bridge for a steel string guitar	20-14
20.3.1. Gluing on a steel string guitar bridge	20-17
20.3.2. Routing a saddle slot with the bridge glued down	20-19 20-19
20.4. Thial actaining of the bridge	20 1.
21. Fitting the Tuners, Nut and Saddle	
21.1. Tuner requirements	
21.2. Fitting sealed tuners on a steel string guitar	
21.3. Fitting slot head tuners on a classical guitar	21-4 21-5
21.5. The nut	
21.5.1. The nut blank	21-6
21.5.2. Machining the compensated nut	
21.5.3. Fitting the nut	
21.6.1. Making the saddle	
21.6.2. Compensating the saddle	
21.6.3. Compensating a conventional saddle	
22. Adjustments	22-2222-2 22-2
22.2. Trouble shooting the string set-up	
22.2.1. Rattles only on open strings	22-3
22.2.2. Rattles that persist over most of the fretboard	22-3
22.2.3. Rattles on particular frets	
22.2.4. Rattles on a range of lower frets	22-3
22.2.6. Removing frets	
22.2.7. Rattles on a classical guitar D (4 <sup>th</sup> ) string	
22.2.8. Buzz on the 4 <sup>th</sup> string of a classical guitar	
22.2.9. Deadness on a classical guitar G (3 <sup>rd</sup> ) string	
22.2.10. Deadness on particular fretted notes	
22.3. Trimming body resonances	
22.3.1.1. Using side masses	
22.3.1.2. By adjusting the back resonant frequency	22-8
22.3.1.3. By adjusting the cavity resonant frequency	22-8
22.3.1.4. By adding mass to or removing mass from the top	
22.3.2. Adjusting the cavity resonance	
22.3.3. Adjusting the back resonance	
23. Reflections	23-2
Appendix I	
A1 1. The shipwright's compass	Δ1 1_1
AT 1. The shipwright's compass	AI 1-1
Appendix II	
A2 1. Fret spacing for common scale lengths	A2 1-1
Glossary	<b>-</b>
Index	
About Trevor and Gerard	
Drawings 1-6 (Envelope inside back cover)	